



## AMF THERMATEX® Thermofon

- AMF THERMATEX® Thermofon features a smooth, white laminated finish and modern design visual. It provides high sound absorption for enhanced acoustic comfort
- High sound absorption (0.80 (H)  $\alpha_w$ )
- Excellent light reflectance (88%)
- ISO 4
- Ideal for offices, classrooms and learning applications



<b>Edge details</b> Additional edge details on request		Board 	Tegular 24/90 	Tegular 15/90 														
<b>Thickness (mm)</b>		15	15	15														
<b>Dimensions (mm)</b> Additional sizes on request		600 x 600 625 x 625 1200 x 600 1250 x 625	600 x 600 625 x 625 1200 x 600	600 x 600 625 x 625 1200 x 600														
<b>System</b>		Exposed demountable - System C																
<b>Weight</b>		2.9 kg / m <sup>2</sup>																
<b>Colour</b>		White																
<b>Sound absorption</b>		EN ISO 354 $\alpha_w = \mathbf{0.80 (H)}$ as per EN ISO 11654 - <b>Class B</b> <table border="1"> <thead> <tr> <th>Frequency f (Hz)</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td><math>\alpha_p</math></td> <td>0.55</td> <td>0.75</td> <td>0.75</td> <td>0.80</td> <td>0.95</td> <td>1.00</td> </tr> </tbody> </table> NRC = <b>0.85</b> as per ASTM C 423			Frequency f (Hz)	125	250	500	1000	2000	4000	$\alpha_p$	0.55	0.75	0.75	0.80	0.95	1.00
Frequency f (Hz)	125	250	500	1000	2000	4000												
$\alpha_p$	0.55	0.75	0.75	0.80	0.95	1.00												
<b>Sound attenuation</b>		EN ISO 10848-2 $D_{n,f,w} = \mathbf{28 dB}$ as per EN ISO 717-1 CAC = <b>29 dB</b> as per ASTM E 413-10																
<b>Sound reduction</b>		EN ISO 10140-2 $R_w = \mathbf{13 dB}$ as per EN ISO 717-1																
<b>Fire reaction</b>		Euroclass <b>A2-s1, d0</b> as per EN 13501-1 <b>Class A</b> as per ASTM E 84 RUS <b>KM1 (G1, V1, D1, T1)</b> as per 123-FZ																
<b>Light reflectance</b>		<b>88%</b>																
<b>Thermal conductivity</b>		$\lambda = \mathbf{0.040 W/mk}$ as per EN 12667																
<b>Humidity resistance</b>		<b>95% RH</b>																
<b>Clean room</b>		<b>ISO 4</b> as per EN ISO 14644-1																
<b>Indoor air quality</b>																		
<b>Cleanability</b>																		
<b>Sustainability</b>																		
		42%																
			<a href="http://www.blauer-engel.de/uz132">www.blauer-engel.de/uz132</a>															

Products may vary from country to country. Please contact your local sales representative. For further information and legal notice, please visit our website.